



- NOTES:
1. POWER SUPPLY: 24VOLT DC, 80 WATT SINGLE SWITCHING, UNIVERSAL AC INPUT, FACTORY MOUNTED JUNCTION BOXES ON INPUT AND OUTPUT ENDS. NRTL LISTED. SUPPLIED BY THE SKY FACTORY.
 2. TB - TERMINAL BLOCK, BARRIER TYPE WITH BINDING SCREW, FOR COPPER WIRE ONLY, WIRE RANGE : #12-#22AWG.
 3. MINIMIZE VOLTAGE DROP BY LOCATING POWER SUPPLIES AS CLOSE AS POSSIBLE TO LUMINOUS VIRTUAL WINDOW. SEE WIRE SIZING CHART IN INSTALLATION MANUAL.
 4. THIS DRAWING APPLIES FOR LVW MODELS: LV2240DR, LV2240DS, LV4022DR, LV4022DS

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE SKY FACTORY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE SKY FACTORY IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	TITLE: LVW V4 LED WIRING DIAGRAM, EXTERNAL POWER SUPPLY 2 WIRE PAIRS (NOTE 4)	
		DIMENSIONS ARE IN INCHES		DRAWN	JE		01-23-11
		TOLERANCES:		CHECKED			
		FRACTIONAL ± 1/32		ENG APPR.			
		ANGULAR: MACH BEND		MFG APPR.			
		TWO PLACE DECIMAL ± 0.015		Q.A.			
		THREE PLACE DECIMAL ± 0.005					
NEXT ASSY	USED ON	INTERPRET GEOMETRIC TOLERANCING PER:		Sky Factory		SIZE	
APPLICATION		MATERIAL		FAIRFIELD, IA		DWG. NO.	
3RD ANGLE		FINISH				REV	
		DO NOT SCALE DRAWING				A	
						LV000887	SHEET 1 OF 1